SIEMENS

Data sheet US2:52SW2CABA1

Selector switch, metal, NEMA 4X Maintained Long lever, C Cam 1NO-1NC left, right 3 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Enclosure		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator		
Material of the actuating element	plastic	
Number of contact modules	1	
Type of unlocking device	rotate-to-unlatch mechanism	
Number of switching positions	3	
Front ring		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
Color of the front ring	black	
General technical data		
Product function		

 positive opening 	Yes
Product component	
• Light source	No
Insulation voltage	
• rated value	600 V
Protection class IP	IP66
• of the terminal	IP20
Operating frequency maximum	600 1/h
Thermal current	10 A

Auxiliary circuit	
Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
• at 110 V rated value	60 A
• at 500 V rated value	12 A

Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
with screw-type terminals	8 lbf·in

Ambient conditions	
Ambient temperature	
 during operation 	-35 +70 °C
during storage	-40 +85 °C

Installation/ mounting/ dimensions	
Shape of the installation opening	round

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SW2CABA1

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52SW2CABA1}$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SW2CABA1

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SW2CABA1&lang=en

11/13/2019 last modified: