

Eaton E57-30GU15-A

Catalog Number: E57-30GU15-A

Inductive Global Proximity Sensor, E57, Straight, 30 mm, Unshielded, Output ON, 6.6 ft, 200 mA at 250V, <3.0% sensing range, PVC, 2-wire AC, NO, 20-250V

General specifications



Product Name	Catalog Number
Eaton E57 inductive proximity sensor	E57-30GU15-A
UPC	Product Length/Depth
782114289068	3.15 in
Product Height	Product Width
1.18 in	1.18 in
Product Weight	Warranty
0.5 lb	1 year
Compliances	Certifications
CE Marked	UL Listed
	CSA Certified

defaultTaxonomyAttributeLabel

Type

E57

Contact Rating

200 mA at 250V

Actuator function

Unshielded

Cable type

Polyvinyl Chloride (PVC)

Accuracy

< 3% sensing range

Enclosure material

Nickel plated brass

Contact configuration

2-wire AC, NO

Series

E57

Environmental rating

IP67, IP69K

Temperature rating

-13 to 158 °F

Cord length

79.2 ft

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Maximum AC current

200 mA

Input voltage

20-250 V

Size

30 mm

LED indicator

Output ON

Resources

Brochures

[Global Series inductive proximity sensors](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

[Product Range Catalog Sensors – products, basic information, applications](#)

Multimedia

[We make what matters](#)

Specifications and datasheets

[Eaton Specification Sheet - E57-30GU15-A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)