



**Part #: F1-4868FLL**

## FEATURES

- Holds up to 12 Splice Sleeves
- Strain Relief for Incoming Cable (Up to 12mm OD)
- Manages and Routes Spare Fiber
- Wall Mountable
- Durable High Impact ABS Enclosure, Dark Gray
- 6.75”H x 4.75”W x 2.125”D

The FIS Splice Enclosure utilizes a 12 position molded splice chip to secure splices in a NEMA 4X enclosure. It is wall mountable and recommended for installation within controlled environments. Cable entry grommets secure incoming and outgoing cable with an outer diameter up to 12mm. Select the correct part number for compatibility with the size of the outer diameter of the cable, and either fusion or mechanical splice chips pre-installed. Internal fiber management guides provide the ability to coil excess fiber within the enclosure.

## SPECIFICATIONS

<b>Material</b>	High Impact ABS
<b>Dimensions</b>	6 ¾”H x 4 ¾”W x 2 1/8”D
<b>Operating Temperature</b>	-40°C to 80°C
<b>Color</b>	Dark Gray (Body)
<b>Weight</b>	0.65 lbs
<b>Capacity</b>	(12) Splice Sleeves
<b>Protection Class</b>	NEMA 4X, Indoor

## ORDERING INFORMATION

<b>F1-4868-FSS</b>	Fusion Splice Enclosure, 12 Position Splice Chip, Accepts Up to 7mm Cable OD
<b>F1-4868-MSS</b>	Mechanical Splice Enclosure, 12 Position Splice Chip, Accepts Up to 7mm Cable OD
<b>F1-4868-FLL</b>	Fusion Splice Enclosure, 12 Position Splice Chip, Accepts 7mm to 12mm Cable OD
<b>F1-4868-MLL</b>	Mechanical Splice Enclosure, 12 Position Splice Chip, Accepts 7mm to 12mm Cable OD