

T-Series™

LIGHTHEAD

ISOLO™ DUO™ TRIO™



The T-Series provides high performance warning or illumination and features a sleek and low-profile design, with a depth of only 0.5”.



TLI3JC
TRIO™

FEATURES

- Available in SOLO™, DUO™, or TRIO™
- Linear Super-LED® optics
- SOLO models available in single-or split-colors
- SOLO (single-color) models have 25 Scan-Lock™ flash patterns, split-color models have 69 Scan-Lock flash patterns
- DUO models have 33 Scan-Lock flash patterns
- TRIO models have 33 Scan-Lock flash patterns
- Hard-coated lenses resist environmental damage from sand, sun, salt, and road chemicals
- Synchronizable to other Whelen sync products
- Surface mount via 2 screws for easy installation
- Black flange included
- 4-wire 6” pigtail cable included
- Smoked lenses available

Clear Lens	
TLI*	Amber, Blue, Red or White
TLI#	Split Red/White, Blue/White, Amber/White, Red/Blue or Blue/Amber
TLI2#	DUO Red/White, Blue/White, Amber/White, Red/Blue or Blue/Amber
TLI3#*	TRIO Red/Blue/Amber, Red/Amber/White, Blue/Amber/White, Red/Blue/White, Red/Amber/Green, Blue/Amber/Green, Green/Amber/White, Red/Green/White or Blue/Green/White
Smoked Lens	
TLI*X	Amber, Blue, Red or White
TLI#X	Split Red/White, Blue/White, Amber/White, Red/Blue or Blue/Amber
TLI2#X	DUO Red/White, Blue/White, Amber/White, Red/Blue or Blue/Amber
XTLI3#*	TRIO Red/Blue/Amber, Red/Amber/White, Blue/Amber/White, Red/Blue/White, Red/Amber/Green, Blue/Amber/Green, Green/Amber/White, Red/Green/White, or Blue/Green/White



Replace * symbol in model number with letter indicating color desired: A = Amber, B = Blue, C = White, R = Red
 Replace # symbol in model number with letter indicating DUO colors desired: D = Red/White, E = Blue/White, F = Amber/White, J = Red/Blue, M = Blue/Amber
 Replace #* symbol in model number with letter indicating TRIO colors desired: KC = Red/Amber/White, KG = Red/Amber/Green, JA = Red/Blue/Amber, JC = Red/Blue/White, LC = Red/Green/White, MC = Blue/Amber/White, MG = Blue/Amber/Green, NC = Blue/Green/White, PC = Green/Amber/White,

SPECS

Voltage: 12 VDC
 Amperage: SOLO: 0.82 amps (peak), 0.33 amps (average)
 DUO: 0.72 amps (peak), 0.28 amps (average)
 TRIO: 0.72 amps (peak), 0.28 amps (average)
 Dimensions: 5.14” (13.06cm) L x 1.50” (3.81cm) H x 0.50” (1.27cm) D
 Certifications: SAE Class 1 Certified
 Warranty: 10-year warranty

OPTIONS

TIONFC	Flange, Chrome
TIONBKT1	“L” Mounting Bracket for 1 Lighthead
TIONBKT2	Universal License Plate Bracket for 2 Lightheads
TIONBKT3	“L” Mounting Bracket for 2 Lightheads
TIONBKT4	Universal Over/Under “L” Mounting Bracket for 2 Lightheads



TLIA with optional Chrome flange
ISOLO™



TLI2J
DUO™



Side View

WARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit whelen.com/regulatory.

All products proudly designed, manufactured, and assembled in the U.S.A.
 • ISO 9001 Registered QMS

Whelen Engineering reserves the right to upgrade and improve products without notice.
 © 2024 Whelen Engineering Company, Inc. Printed in U.S.A.
 Code No. P12959L - 02/2024

WHELEN®
 MANUFACTURED IN AMERICA

51 Winthrop Road
 Chester, Connecticut 06412-0684
 (860) 526-9504
www.whelen.com